

ビニール端末キャップ



特長

■圧着端子使用時の絶縁用にご使用下さい。

■以下の特注品の製作も可能です。

- ・キャップ
- ・脱塩ビ品
- ・耐熱用塩化ビニールUL94V-0

材質

■塩化ビニル



仕様

型番	D1φ	D2φ	D3φ	L1±0.5	L2	L±1	T±0.3	単位
V-0.3	2.6	3.0	2.0	6.0	7.0	13.0	0.8	1,000
V-1.25	2.8	3.3	3.1	6.0	7.0	13.0	0.8	1,000
V-2	3.3	4.5	3.7	7.0	7.0	14.0	1.0	1,000
V-3.5	4.2	5.7	4.3	9.0	8.0	17.0	1.0	1,000
V-5.5	4.8	5.7	5.2	9.0	8.0	17.0	1.0	1,000
V-8	6.2	7.2	6.2	10.0	9.0	19.0	1.0	1,000
V-14	7.5	10.0	8.0	14.0	11.0	25.0	1.1	100
V-22	10.5	12.0	9.5	15.0	15.0	30.0	1.2	100
V-38	12.5	14.0	11.8	17.5	16.5	34.0	1.5	100
V-60	15.0	16.8	13.5	20.0	19.0	39.0	1.5	100
V-80	17.0	19.0	16.0	25.0	22.0	47.0	1.6	100
V-100	19.0	22.0	18.0	30.0	24.0	54.0	1.7	50
V-125	21.0	24.0	20.0	32.0	25.0	57.0	1.8	50
V-150	23.0	24.5	22.0	35.0	30.0	65.0	2.0	25
V-200	27.0	32.0	24.0	35.0	30.0	65.0	2.0	20
V-250	29.0	38.0	26.5	35.0	40.0	77.0	2.5	20
V-325	29.0	38.0	29.0	37.0	42.0	77.0	2.5	20

寸法図

